

# Safety Data Sheet

Issue Date: 26-Jan-2009

Revision Date: 03-Aug-2015

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** Type D Black Ink

### Other means of identification

**SDS #** USM-001

**Product Code** IU-D14, IU-D1PT, IU-D1QT, IU-D1QTH, IU-D1GL  
**UN/ID No** UN1210

### Recommended use of the chemical and restrictions on use

**Recommended Use** Printing ink.

### Details of the supplier of the safety data sheet

#### **Manufacturer/Supplier**

Universal Stenciling & Marking Systems, Inc.  
205 15th Avenue S.E.  
St. Petersburg, FL 33701  
PH: 727-894-3027

### Emergency Telephone Number

**Emergency Telephone (24 hr)** Chemtrec 1-800-424-9300 (North America) 1-703-527-3887 (International)

## 2. HAZARDS IDENTIFICATION

**Appearance** Black liquid

**Physical State** Liquid

**Odor** Alcohol

### Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Flammable Liquids	Category 3

### Signal Word

**Danger**

### Hazard Statements

Harmful if swallowed  
Harmful in contact with skin  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye damage  
Flammable liquid and vapor



#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a poison center or doctor/physician  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 Call a poison center or doctor/physician if you feel unwell  
 If skin irritation occurs: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a poison center or doctor/physician if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Rinse mouth  
 IN CASE OF FIRE: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Other Hazards**

Harmful to aquatic life with long lasting effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethylene Glycol Monobutyl Ether	111-76-2	30-40
n-Propyl Alcohol	71-23-8	10-20
Ethyl Alcohol	64-17-5	10-20
Carbon Black	1333-86-4	1-10

\*\*If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

## 4. FIRST-AID MEASURES

### First Aid Measures

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Get immediate medical advice/attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If irritation persists or feeling unwell, obtain medical advice.
<b>Inhalation</b>	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
<b>Ingestion</b>	Do not induce vomiting without medical advice. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

### Most important symptoms and effects

<b>Symptoms</b>	Causes skin irritation and serious eye damage. May cause irritation to the mucous membranes and upper respiratory tract.
-----------------	--

### Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water fog or fine spray, carbon dioxide, dry chemical or foam.

**Unsuitable Extinguishing Media** Direct water stream may spread fire.

### Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors may travel to source of ignition and flash back.

**Hazardous Combustion Products** Carbon oxides.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames. Take precautionary measures against static discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Personal Precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition & ventilate area. Evacuate unnecessary personnel.
<b>Environmental Precautions</b>	See Section 12 for additional Ecological Information.

### Methods and material for containment and cleaning up

<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.
--------------------------------	---

**Methods for Clean-Up**

Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on Safe Handling**

Handle in accordance with good industrial hygiene and safety practice. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when handling this product. Use personal protection recommended in Section 8. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Ground/bond container and receiving equipment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Keep container tightly closed. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Keep container tightly closed and store in a cool, dry and well-ventilated place.

**Incompatible Materials**

Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
n-Propyl Alcohol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 500 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 625 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 200 ppm TWA: 500 mg/m <sup>3</sup> STEL: 250 ppm STEL: 625 mg/m <sup>3</sup>
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Carbon Black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

**Appropriate engineering controls**

**Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Maintain eye wash fountain and quick-drench facilities in work area. Local exhaust ventilation recommended.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Use safety glasses or chemical splash goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

- Skin and Body Protection**      Gloves are recommended. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
  
- Respiratory Protection**      MSHA/ NIOSH-approved vapor respirator is recommended with handling in areas where adequate ventilation is not available. Refer to 29 CFR 1910.134 for respiratory protection requirements.
  
- General Hygiene Considerations**      Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<p><b>Physical State</b>  <b>Appearance</b>  <b>Color</b></p>	<p>Liquid                  Black liquid                  Black</p>	<p><b>Odor</b>  <b>Odor Threshold</b></p>	<p>Alcohol                  Not determined</p>
---	--	---	--

  

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	Not determined	
Flash Point	24.72 / 76.5 °F	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Heavier than air	(Air=1)
Specific Gravity	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content (%)	71.05	
Density	7.72 lbs/gal	

**10. STABILITY AND REACTIVITY**

**Reactivity**

Not reactive under normal conditions.

**Chemical Stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to Avoid**

Heat, sparks and open flames.

**Incompatible Materials**

Strong oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

<b>Eye Contact</b>	Causes serious eye damage.
<b>Skin Contact</b>	Causes skin irritation. Harmful in contact with skin.
<b>Inhalation</b>	Harmful if inhaled.
<b>Ingestion</b>	Harmful if swallowed.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
n-Propyl Alcohol 71-23-8	= 1870 mg/kg ( Rat )	= 4049 mg/kg ( Rabbit )	> 13548 ppm ( Rat ) 4 h
Ethyl Alcohol 64-17-5	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-

**Information on physical, chemical and toxicological effects**

**Symptoms** Please see section 4 of this SDS for symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Carcinogenicity** Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	A3	Group 3		
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X
Carbon Black 1333-86-4	A3	Group 2B		X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Numerical measures of toxicity**

Not determined

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

**Component Information**

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylene Glycol Monobutyl Ether 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50
n-Propyl Alcohol 71-23-8		4480: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 17700 mg/L 5 min EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	3642: 48 h Daphnia magna mg/L EC50 3339 - 3977: 48 h Daphnia magna mg/L EC50 Static
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50

**Persistence/Degradability**

Not determined.

**Bioaccumulation**

Not determined.

**Mobility**

Chemical Name	Partition Coefficient
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
n-Propyl Alcohol 71-23-8	0.25 - 0.34
Ethyl Alcohol 64-17-5	-0.32

**Other Adverse Effects**

Not determined

**13. DISPOSAL CONSIDERATIONS**

**Waste Treatment Methods**

**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**US EPA Waste Number**

D001

**California Hazardous Waste Status**

Chemical Name	California Hazardous Waste Status
n-Propyl Alcohol 71-23-8	Toxic Ignitable
Ethyl Alcohol 64-17-5	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

**DOT**

UN/ID No UN1210  
 Proper Shipping Name Printing ink  
 Hazard Class 3  
 Packing Group III

**IATA**

UN/ID No UN1210  
 Proper Shipping Name Printing ink  
 Hazard Class 3  
 Packing Group III

**IMDG**

UN/ID No UN1210  
 Proper Shipping Name Printing ink  
 Hazard Class 3  
 Packing Group III

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethylene Glycol Monobutyl Ether	Present	X		Present		Present	X	Present	X	X
n-Propyl Alcohol	Present	X		Present		Present	X	Present	X	X
Ethyl Alcohol	Present	X		Present		Present	X	Present	X	X
Carbon Black	Present	X		Present	Present	Present	X	Present	X	X

**Legend:**

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

**US Federal Regulations**

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).



**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	30-40	1.0

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental
Carbon Black - 1333-86-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
n-Propyl Alcohol 71-23-8	X	X	X
Ethyl Alcohol 64-17-5	X	X	X
Carbon Black 1333-86-4	X	X	X

**16. OTHER INFORMATION****NFPA****Health Hazards**

Not determined

**Flammability**

Not determined

**Instability**

Not determined

**Special Hazards**

Not determined

**HMIS****Health Hazards**

2

**Flammability**

3

**Physical Hazards**

0

**Personal Protection**

Not determined

Issue Date: 26-Jan-2009

Revision Date: 03-Aug-2015

Revision Note: New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**