# **Safety Data Sheet**

Issue Date: 24-Feb-2009 Revision Date: 11-Aug-2015 Version 1

# 1. IDENTIFICATION

Product Identifier

Product Name Type D N.L. Yellow Ink

Other means of identification

**SDS** # USM-004

Product Code IU-D5NL4, IU-D5NLQT, IU-D5NLQTH, IU-D5NLGL

UN/ID No UN1210

Recommended use of the chemical and restrictions on use

Recommended Use Printing ink.

Details of the supplier of the safety data sheet

Manufacturer/Supplier

Universal Stenciling & Marking Systems, Inc.

205 15th Avenue S.E. St. Petersburg, FL 33701 PH: 727-894-3027

**Emergency Telephone Number** 

Emergency Telephone (24 hr) Chemtrec 1-800-424-9300 (North America) 1-703-527-3887 (International)

# 2. HAZARDS IDENTIFICATION

Appearance Yellow liquid Physical State Liquid Odor Alcohol

#### Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Flammable Liquids	Category 2

### **Hazards Not Otherwise Classified (HNOC)**

May be harmful in contact with skin

# Signal Word

Danger

# **Hazard Statements**

Harmful if swallowed
Harmful if inhaled
Causes skin irritation
Causes serious eye damage
May cause cancer
Highly flammable liquid and vapor



### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a poison center or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

# Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### **Other Hazards**

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical Name	CAS No	Weight-%
Ethylene Glycol Monobutyl Ether	111-76-2	30-40
Ethyl Alcohol	64-17-5	20-30
Titanium dioxide	13463-67-7	10-20
Pigment Yellow	5468-75-7	1-5
n-Propyl Alcohol	71-23-8	1-10

<sup>\*\*</sup>If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.\*\*

### 4. FIRST-AID MEASURES

#### **First Aid Measures**

**Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Get immediate medical advice/attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If irritation persists or

feeling unwell, obtain medical advice.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison

center if individual's condition declines or if symptoms persist.

**Ingestion** Do not induce vomiting without medical advice. Rinse mouth thoroughly with water. Never

give anything by mouth to an unconscious person. Seek medical attention immediately.

Revision Date: 11-Aug-2015

#### Most important symptoms and effects

Symptoms Causes skin irritation and serious eye damage. May cause irritation to the mucous

membranes and upper respiratory tract.

# Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

# Suitable Extinguishing Media

Water fog or fine spray, carbon dioxide, dry chemical or foam.

Unsuitable Extinguishing Media Direct water stream may spread fire.

# **Specific Hazards Arising from the Chemical**

Highly flammable liquid and vapor. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products Carbon oxides.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames. Take precautionary measures against static

discharge.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Remove all

sources of ignition & ventilate area. Evacuate unnecessary personnel.

**Environmental Precautions** See Section 12 for additional Ecological Information.

# Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert

(i.e. vermiculite, dry sand or earth) absorbent material.

**Methods for Clean-Up** Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material

and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste

disposal, see section 13 of the SDS.

# 7. HANDLING AND STORAGE

# Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special

instructions before use. Do not handle until all safety precautions have been read and understood. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when handling this product. Use personal protection recommended in Section 8. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Ground/bond container and receiving equipment. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Keep container tightly closed. Take precautionary measures

against static discharges. Avoid contact with skin, eyes or clothing.

# Conditions for safe storage, including any incompatibilities

Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked **Storage Conditions** 

**Incompatible Materials** Strong oxidizing agents.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene Glycol Monobutyl Ether	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m <sup>3</sup>	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m <sup>3</sup>
		(vacated) TWA: 120 mg/m <sup>3</sup>	
		(vacated) S*	
		S*	
Ethyl Alcohol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		(vacated) TWA: 1900 mg/m <sup>3</sup>	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m <sup>3</sup> total	_
		dust	

n-Propyl Alcohol
71-23-8

TWA: 100 ppm
TWA: 200 ppm
TWA: 500 mg/m³
(vacated) TWA: 200 ppm
TWA: 200 ppm
TWA: 200 ppm
TWA: 200 ppm
(vacated) TWA: 200 ppm
(vacated) TWA: 500 mg/m³
STEL: 250 ppm
(vacated) STEL: 250 ppm
(vacated) STEL: 625 mg/m³

### Appropriate engineering controls

**Engineering Controls**Apply technical measures to comply with the occupational exposure limits. Maintain eye

wash fountain and guick-drench facilities in work area. Local exhaust ventilation

Revision Date: 11-Aug-2015

recommended.

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection Use safety glasses or chemical splash goggles. Refer to 29 CFR 1910.133 for eye and face

protection regulations.

**Skin and Body Protection** Gloves are recommended. Refer to 29 CFR 1910.138 for appropriate skin and body

protection.

Respiratory Protection MSHA/ NIOSH-approved vapor respirator is recommended with handling in areas where

adequate ventilation is not available. Refer to 29 CFR 1910.134 for respiratory protection

requirements.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

reuse.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

 Physical State
 Liquid

 Appearance
 Yellow liquid
 Odor
 Alcohol

Color Yellow Odor Threshold Not determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** Not determined

Melting Point/Freezing Point

Boiling Point/Boiling Range

Not determined

Not determined

Flash Point 17.77 °C / 64 °F ASTM D3828-05

Evaporation Rate
Flammability (Solid, Gas)
Upper Flammability Limits
Not determined
Not determined
Not determined
Not determined

Vapor PressureNot determinedVapor DensityHeavier than air(Air=1)

Specific Gravity
Water Solubility
Not determined
Solubility in other solvents
Partition Coefficient
Auto-ignition Temperature
Decomposition Temperature
Kinematic Viscosity
Not determined
Not determined
Not determined
Not determined
Not determined

Kinematic Viscosity

Dynamic Viscosity

Explosive Properties

Oxidizing Properties

Not determined
Not determined
Not determined

 VOC Content (%)
 67.75

 Density
 8.34 lbs/gal

# 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

# **Chemical Stability**

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

# **Conditions to Avoid**

Heat, sparks and open flames.

# **Incompatible Materials**

Strong oxidizing agents.

# **Hazardous Decomposition Products**

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Product Information** 

Causes serious eye damage. **Eye Contact** 

**Skin Contact** Causes skin irritation. May be harmful in contact with skin.

Inhalation Harmful if inhaled.

Ingestion Harmful if swallowed.

# Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol Monobutyl Ether	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
111-76-2			
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Pigment Yellow 5468-75-7	> 5 g/kg (Rat)	-	-
n-Propyl Alcohol 71-23-8	= 1870 mg/kg (Rat)	= 4049 mg/kg (Rabbit)	> 13548 ppm (Rat)4 h

# Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Carcinogenicity

May cause cancer. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether 111-76-2	А3	Group 3		
Ethyl Alcohol 64-17-5	A3	Group 1	Known	Х
Titanium dioxide 13463-67-7		Group 2B		Х
Pigment Yellow 5468-75-7		Group 1	Known	Х

### Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

# **Numerical measures of toxicity**

Not determined

# 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Toxic to aquatic life with long lasting effects.

# Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylene Glycol Monobutyl		1490: 96 h Lepomis		1000: 48 h Daphnia magna
Ether		macrochirus mg/L LC50		mg/L EC50 1698 - 1940: 24
111-76-2		static 2950: 96 h Lepomis		h Daphnia magna mg/L
		macrochirus mg/L LC50		EC50
Ethyl Alcohol		12.0 - 16.0: 96 h	EC50 = 34634 mg/L 30 min	9268 - 14221: 48 h Daphnia
64-17-5		Oncorhynchus mykiss mL/L	EC50 = 35470 mg/L 5 min	magna mg/L LC50 2: 48 h
		LC50 static 13400 - 15100:		Daphnia magna mg/L EC50
		96 h Pimephales promelas		Static 10800: 24 h Daphnia
		mg/L LC50 flow-through 100:		magna mg/L EC50
		96 h Pimephales promelas		
		mg/L LC50 static		
n-Propyl Alcohol		4480: 96 h Pimephales	EC50 = 17700 mg/L 5 min	3642: 48 h Daphnia magna
71-23-8		promelas mg/L LC50	EC50 = 45000  mg/L  5  h	mg/L EC50 3339 - 3977: 48
		flow-through	EC50 = 8686 mg/L 15 min	h Daphnia magna mg/L
		_	EC50 = 980  mg/L  12  h	EC50 Static

### Persistence/Degradability

Not determined.

### **Bioaccumulation**

Not determined.

,

Revision Date: 11-Aug-2015

#### Mobility

Chemical Name	Partition Coefficient
Ethylene Glycol Monobutyl Ether	0.81
111-76-2	
Ethyl Alcohol	-0.32
64-17-5	
n-Propyl Alcohol	0.25 - 0.34
71-23-8	

### **Other Adverse Effects**

Not determined

# 13. DISPOSAL CONSIDERATIONS

### **Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

### **US EPA Waste Number**

D001

# California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Ethyl Alcohol	Toxic
64-17-5	Ignitable
n-Propyl Alcohol	Toxic
71-23-8	Ignitable

# 14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT

UN/ID No UN1210
Proper Shipping Name Printing ink

Hazard Class 3

Packing Group

**IATA** 

UN/ID No UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group ||

**IMDG** 

UN/ID No UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group II

# 15. REGULATORY INFORMATION

# International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethylene Glycol Monobutyl Ether	Present	Х		Present		Present	Х	Present	X	Х
Ethyl Alcohol	Present	Х		Present		Present	Х	Present	Х	Х
Titanium dioxide	Present	Х		Present		Present	Х	Present	Х	Х
Pigment Yellow	Present	Х		Present		Present	Х	Present	Х	Х
n-Propyl Alcohol	Present	Х		Present		Present	Х	Present	X	Х

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### US Federal Regulations

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

# SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	30-40	1.0

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

### US State Regulations

# **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen
	Developmental
Titanium dioxide - 13463-67-7	Carcinogen
Pigment Yellow - 5468-75-7	Carcinogen

### **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Ethyl Alcohol 64-17-5	X	X	Х
Titanium dioxide 13463-67-7	X	X	Х
n-Propyl Alcohol 71-23-8	X	X	X

# **16. OTHER INFORMATION**

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
HMIS_	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	0	Not determined

24-Feb-2009 Issue Date: **Revision Date:** 11-Aug-2015 **Revision Note:** New format

# Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**